



Luminaire list								
Index	Manufacturer	Article name	Item number	Luminous flux	Light loss factor	Connected load	Quantity	Mounting Height
A	Access Fixtures	230V 50Hz 600W	STAK AF77XST-RSL600S 25'	70760 lm	0.80	618.1 W	26	70'

Name	Parameter	Min	Max	Average	Mean/Min	Max/Min
Target Green 1	Perpendicular Illuminance (Adaptive)	8.51 fc	12.4 fc	10.0 fc	1.18	1.46
Target Green 2	Perpendicular Illuminance (Adaptive)	8.75 fc	16.4 fc	12.4 fc	1.41	1.87
Target Green 3	Perpendicular Illuminance (Adaptive)	10.8 fc	19.2 fc	14.1 fc	1.31	1.78
Target Green 4	Perpendicular Illuminance (Adaptive)	11.4 fc	16.1 fc	13.7 fc	1.20	1.41
Target Green 5	Perpendicular Illuminance (Adaptive)	9.12 fc	17.2 fc	12.8 fc	1.40	1.89
Target Green 6	Perpendicular Illuminance (Adaptive)	6.70 fc	10.6 fc	9.22 fc	1.38	1.59
Target Green 7	Perpendicular Illuminance (Adaptive)	7.19 fc	11.1 fc	8.92 fc	1.24	1.54
Target Green 8	Perpendicular Illuminance (Adaptive)	9.80 fc	16.8 fc	13.1 fc	1.34	1.71
Target Green 9	Perpendicular Illuminance (Adaptive)	9.22 fc	13.8 fc	11.2 fc	1.21	1.50
Target Green 10	Perpendicular Illuminance (Adaptive)	6.89 fc	11.6 fc	8.78 fc	1.27	1.68
Target Green 11	Perpendicular Illuminance (Adaptive)	9.23 fc	13.7 fc	11.2 fc	1.21	1.49
Distance Marker 1 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	27.1 fc	27.1 fc	27.1 fc	1.000	1.000
Distance Marker 2 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	15.0 fc	15.6 fc	15.3 fc	1.019	1.039
Distance Marker 3 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	32.1 fc	32.7 fc	32.4 fc	1.008	1.016
Distance Marker 4 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	27.2 fc	28.4 fc	27.8 fc	1.021	1.042
Distance Marker 5 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	11.7 fc	12.1 fc	11.9 fc	1.014	1.028
Distance Marker 6 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	16.9 fc	18.2 fc	17.5 fc	1.039	1.08
Distance Marker 7 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	10.9 fc	11.0 fc	10.9 fc	1.003	1.006
Distance Marker 8 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	9.43 fc	9.58 fc	9.50 fc	1.007	1.015
Distance Marker 9 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	27.3 fc	27.9 fc	27.6 fc	1.010	1.020
Distance Marker 10 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	22.7 fc	22.7 fc	22.7 fc	1.001	1.002
Distance Marker 11 (Vertical Illuminance)	Perpendicular Illuminance (Adaptive)	27.2 fc	27.7 fc	27.4 fc	1.010	1.020